# Model Q-8 Loudspeaker

# Offering high sensitivity & power handling capabilities

The Model Q-8 is more robust than our compact Soundsphere loudspeakers models, offering greater sensitivity and power-handling capability. The Q-8 was designed to provide clear voice announcements and high-fidelity foreground and background music for applications such as restaurants, courtrooms, churches, shopping centers and airports.

The Q-8 offers Soundsphere's trademark hemispherical coverage pattern and is distinguished by its high sensitivity (94dB 1W/1m) and high power handling capability (100 watts RMS). The Q-8 is available for either surface or hanging mounts, in both standard and custom colors.






# **MODEL Q-8 APPLICATIONS:**

- Restaurants
- Bars & Nightclubs
- Hotel Lobbies & Atriums
- Factories
- Courtrooms
- Gymnasiums
- Educational Facilities
- Churches
- Retail Stores
- Shopping Centers
- Airports

And applications where clear voice announcements and high-fidelity music are required.

#### **Q-8 Technical Data**







MODEL Q-8 SPECIFICATIONS:	
Sensitivity:	94dB SPL; 1 Watt/1 meter
Maximum SPL:	114dB SPL; 1 meter
Power Handling:	100 Watts RMS
Frequency Response:	55Hz to 17kHz ± 6dB
Coverage:	180° vertical 360° horizontal
Rated Impedance:	8 ohms
Weight:	22 lbs. (10 kg)
	1
Size:	Height: 19" (485mm)  Sphere Diameter: 16" (406mm)  Reflector Diameter: 20" (508mm)
Size:  Driver:	Sphere Diameter: 16" (406mm)

	Constructed of inorganic materials impervious to environmental contaminants (weather, ozone, UV, chlorine, salt, etc.)
Material:	Enclosure and reflector are fiberglass with gelcoat finish; rust-resistant hardware
MODEL Q-8 SAMPLE INSTALLATIONS:	
Manufacturing Plants: 1 // 2	
<u>Church</u>	
Courtroom	
Health Club	
Shopping Mall	

### **Model Q-8 Accessories**





Hanging Kit - Order No. HK

Mounting Bracket - Order No. MBM

# **Line Matching Transformer – Order No. TX100**

The Model TX100 is a 100 watt line matching transformer for the Model Q-8 with taps for 25V, 70V, and 100V constant voltage systems. The Model TX100 is factory-mounted in the reflector of the Model Q-8, and its low profile permits the use of the Q8HK hanging kit or the Q8MB mounting bracket. Connection to system wiring is via color-coded flying leads. Available taps: 25V-25W, 12.5W; 70V and 100V-100W, 50W, 25W, 12.5W.